



The spading machine with a bigger capacity and higher permissible weight, with a spader capacity of 80 to 100 HP.



The FarmaX Perfect II is a middle class spading machine, perfectly suited for the use on lighter soils for the medium-sized company in the agri- and horticulture.

This spader comes in various working widths and can easily be fitted with a hydraulically adjustable rotary harrow, rotary cultivator, ring roller, tube roller or packerwals. Regardless of the soil type, the Perfect II guarantees you the best bed for sowing or planting!

Digging and sowing in one operation

The Perfect II can be combined with a sowing machine so as to perform all the required operations in one step. The sowing machine is easily attached using a number of fixed mounting points, but you can also opt for a top-mounted lift to bring the sowing machine closer to the tractor. These combination possibilities help to save fuel.



Versatile and easy to maintain

The spader is designed for perfect ease of maintenance. It also incorporates inspection hatches in the chain case for easy monitoring of the condition of the chain transmission. Thanks to the compact structure of the Perfect II, the machine's centre of gravity lies close to your tractor.

The PE covering prevents the machine getting blocked up. With this spader, structural damage, such as a plough pan or compaction of the subsoil, is a thing of the past. Altogether, this results in a 10-20% increase in crop yield.

Drive to main axle (rotor): Transmission case with differential

Capacity: Up to 2,96 acres (1.2 hectare) per hour in optimum conditions

Power take-off revs: 540 r.p.m.

Tractor power: 80 to 100 HP

Advantages

- easily combined with other machinery
- high capacity
- compact, low-maintenance and user-friendly design
- PE coverage to prevent blockage
- suitable for multiple soil types, from sand to light clay



Compact construction



Option: Top-mounted lift



Combination with sowing machine and top-mounted lift



High-yield transmission case

Technical Data

type	operating width	max. operating depth	standard weight	required power kW/HP	number of spades
Perfect II 250	98.43" – 250 cm	17.72" – 45 cm	3,638 Lbs – 1.650 kg	60/80	18
Perfect II 275	108.27" – 275 cm	17.72" – 45 cm	3,968 Lbs – 1.800 kg	65/90	21
Perfect II 300	118.11" – 300 cm	17.72" – 45 cm	4,740 Lbs – 2.150 kg	80/100	24

MANUFACTURER

FarmaX metaaltechniek BV
Nijverheidsstraat 5
7591 BM Denekamp (NL)
Tel: +31 (0)541-351267
www.farmax.info

FOLLOW US



YOUR DEALER