



A trailed spader with an operating width of 14.76 feet (4,5 m), specially designed for heavy sand and clay soils.



The Farmax Rapide Trailed is a trailed spader with an operating width of no less than 14.76 feet (4,5 m).

The Rapide Trailed can hold its own in all conditions, with an excellent tilling result and exceptional capacity. With a maximum tilling depth of 15.75 inches (40 cm) the Rapide Trailed tills heavy sand and clay soils quickly and without problems.

Consistent rotavation depth, optimum groundwater management

The Rapide Trailed is equipped as standard with a tyre roller consisting of two arrays of 8 tyres. This tyre roller guarantees a consistent rotavation depth and ensures that the ground is properly rolled after tilling. Furthermore, it ensures perfect restoration of groundwater management.



Super fast and extra manoeuvrable

Thanks to a relatively high spading speed and the width of the spader there is a feasible capacity of 6.9 acres (2.8 hectares) per hour. The drive line is designed in such a way that the rotor can easily continue to turn, even when the machine is at an oblique angle behind the tractor. The implementation of the drive line is extra heavy, as usual by the FarmaX Rapide series.

Total weight: 16,534 Lbs (7.500 kg)

Drive: transmission case fitted with differential, extra heavy-duty drive line

Capacity: up to 6.9 acres (2.8 hectares) per hour

Power take-off revs: 1,000 r.p.m.

Tractor power: 200 to 300 HP

Advantages

- extra high capacity, thanks to very wide span
- low maintenance and very user-friendly
- tills heavy sand and clay soils without any problem
- specially designed tyre roller restores the groundwater management and guarantees consistent rotavation depth



The spader blades are attached with shearing bolts



enormous capacity



Sturdy construction



Fitted with 16 roller tyres

Technical Data

type	operating width	max. operating depth	standard weight	required power kW/HP	number of spades	tyre roller
Rapide Trailed	177.17" - 450 cm	15.75" - 40 cm	16,534 Lbs - 7.500 kg	149/200	36	K8,3x24

MANUFACTURER

FarmaX metaaltechniek BV
Nijverheidsstraat 5
7591 BM Denekamp (NL)
Tel: +31 (0)541-351267
www.farmaX.info

FOLLOW US



YOUR DEALER

