



The Farmax Ringseeder, more effective work with higher quality results. The Ringseeder enables contractors to create an even seedbed with a high capacity.



The Farmax Ringseeder has been developed in consultation with actively involved farm contractors, for this reason Farmax has managed to develop a sowing combination that meets the needs of contractors who perform a lot of sowing work.

More compact

The Ringseeder is mounted more compactly on the power harrow due to its parallel guidance, which means that the machine hardly drags in the bends during the sowing work. This also has the advantage that the weight is mounted closer to the tractor.

Better seedbed

The double ringrolers who are attached to the Farmax Ringseeder spreads the seed via a seedbar over the whole working width. The Ringseeder is attached via a parallel guidance to the power harrow. Because of this, the power harrow leans on both ringrolers which ensures a greater pressure on these rolers. This means that soil moisture is better retained around the seed. In addition, the seed is also brought better into contact with the moist soil. The Ringseeder is also equipped with folding side rollers. These side rollers ensure an even seed bed between the work passes, which blends better into each other.



More simple

The experience of farm contractors is that customers can easily work the crop stubble themselves using a cultivator, after which the farm contractor sows the field with the sowing combination. In addition, there is no need to plow or level out the field before using the Ringseeder to create an even seedbed. Another additional advantage is the way of sowing. The seed falls between the power harrow and the ring rollers, without using a harrow or coulter. As a result, crop residues are not taken along during sowing and the seed pattern is not disturbed.

Benefits

- Very manoeuvrable.
- Easy operation.
- Solid, low maintenance design.
- Saves work passes (plowing/grading).
- No smearing from crop residues.

- More compact to the tractor.
- The folding side rollers provide a smoother seed pattern.
- The power harrow rests on the rollers, which presses the seed better in the soil.
- Seed is placed in front of the ring rollers.

Available with: power harrow

Transmission rollers: chain

Ring diameter: 60 cm/23,62 inch

Spindle roller diameter: 45 cm/17,72 inch

Weight: 1350 kg/2976 lbs (basic)

Maximum working width: 3 meter/9ft 10inch

(other dimensions possible)

Length: 1,98 m/6ft 6in

Height: 1,04 m/3ft 5in.

Lights: LED



Equipped with LED lighting



Equipped with stairs



Full field sowing



Foldable side rollers

MANUFACTURER

Farmax metaaltechniek BV
Nijverheidsstraat 5
7591 BM Denekamp (NL)
Tel: +31 (0)541-351267
www.farmax.info

FOLLOW US



YOUR DEALER